



## COMPANÍA GENERAL DE LUBRICANTES SA

C/ Comercio, 36 – Polígono Industrial Can Sunyer  
08740 SANT ANDREU DE LA BARCA ( Barcelona )  
Telf: +34 93 6821514 – Fax: +34 93 6820055  
e-mail: gro@cogelsa.com

## TECHNICAL DATA SHEET

### GS – 3 DIESEL 15W40

**GS-3 DIESEL 15W40** is a special multigrade lubricant for turbocompressed or atmospheric diesel engines. Due to its special additive package it shows a high cleaning and dispersion capability. Specially designed for engines working at high loads and extreme temperature conditions. (Heavy Transport, Public Works Machinery, Marine Engines and Static Engines).

**GS-3 DIESEL 15W40** has been designed technologically to bring the following results:

- High thermal stability, allowing work at high temperatures.
- Superior quality. It facilitates the cold start of the engine and it improves the lubrication process in cold and hot temperatures.
- It prevents sludge formation and deposits. Low ash content.
- It prevents cylinder sleeve deterioration.
- Very resistant to tear and wear, it ensures a longer life span for engines.
- Superior antioxidant, anticorrosive, antirust and antifoaming power.
- High cleaning – dispersion capacity.

SAE Degree	15W40
Viscosity at 100°C	14,4 cSt.
Viscosity at 40°C	115 cSt.
Viscosity Index	138
Pour point	-24°C
Flash point	226°C
TBN	7 mg KOH/g

#### It complies with the norms:

API-CF-4 / SG  
ACEA A2 / E2 / B2  
MB-228.1  
MAN 271  
VOLVO VDS  
MACK EO-K2

MTU TYPE 1  
DEUTZ DQC I-02  
CATERPILLAR TO-2 1K,1N

REV:08/12

Assessment with respect to the elaboration and utilization of “plannings” for the control and conservation of plants and industrial equipment. COMPANÍA GENERAL DE LUBRICANTES S.A. is not accountable for the legal actions arised from the inadequate use of the product or products, herein referred to, being, according to our criteria, correct and complying with the quoted DESCRIPTIONS and APPLICATIONS contained herein.

COMPANY CERTIFIED

